

 **User-friendly, responsive and accurate tester.**

## FEATURES

**Battery 12 V** : test of the voltage and state of charge.





## INSTANT ANALYSIS

- Battery voltage (7 V to 15 V)
- State of charge   

## BATTERY TYPES

- Compatible with multiple types of lead-acid batteries from 20 to 150 Ah :
  - Sealed batteries VRLA / GEL / AGM
  - Standard liquid batteries

### Operating range :

-  EN : 185 > 1125 CCA
-  DIN : 110 > 670 CCA
-  SAE : 200 > 1200 CCA
-  IEC : 130 > 790 CCA (international standard)
- CA/MCA : 240 > 1440 CCA (marine battery)



Supplied in blister transparent packaging






## ACCURATE

Advanced dynamic resistance measurement technology minimises battery discharge and displays an accurate result which is not affected by :

- surface charge
- parasitic load (lights, various indicators, etc)
- contact imperfections (worn out terminals/ lugs, unfastened lugs, etc)

## PRACTICAL

- Digital display
- Protected against polarity reversal
- ABS case (acid resistant)
- Power supply : no internal battery, will power up using the vehicle battery.

		TEST						
Battery	Ah	Battery A	Battery V					
12 V	20>150 Ah	•	• min 7 V	1 s	instant	70 x 15 x 120	50 cm	0.25