



Accurate and user-friendly multifunction tester with backlit LCD screen.

FEATURES

- **Battery 12 V** : test of the voltage and state of charge.
- **Starter 12 V** : test of the start voltage.
- **Alternator 12 V** : tests no load voltage and charging voltage as well as current undulation during the charge.

INSTANT ANALYSIS

- Battery voltage (4.5 V to 16 V)
- Available starting power
- Charge state and battery health (%)

BATTERY TYPES

- Compatible with multiple types of lead-acid batteries from 4 to 150 Ah :
 - VRLA / GEL / AGM sealed batteries
 - STANDARD LIQUID batteries

■ Operating range :

- EN : 185 > 1125 CCA
- DIN : 20 > 670 CCA
- SAE : 40 > 1200 CCA
- IEC : 25 > 790 CCA (international standard)
- CA/MCA : 70 > 1440 CCA (marine battery)



Supplied in transparent packaging

ACCURATE

- The advanced dynamic resistance measurement technology minimises battery discharge and displays an accurate result that is not affected by :
- surface charge
 - parasitic load (lights, various indicators, etc)
 - contact imperfections (worn out terminals/ lugs, unfastened lugs, etc)

PRACTICAL

- LCD display
- Protected against polarity reversal
- ABS case (acid resistant)
- Power supply : Powered by the vehicle battery, no internal battery required.

		TEST			RESULT		mm		kg
Battery		Battery A	Battery V	CHARGING & STARTING SYSTEM VEHICLE					
12 V	4 > 150 Ah	•	• min 4.5 V	12 V	1 s	instant	120 x 79 x 227	50 cm	0.25