# **GYSPACK PRO 900**

Ref. 027084 Ref. 027954

12V



Professional autonomous starter with integrated charger for starting all vehicles equipped with 12 V batteries.

### A high-performance stand-alone starter

Equipped with a **\*high performance\*** lead battery (in start-up: 830A at 1V/c and 3100A at battery peak), the Gyspack PRO 900 is ideal for starting up light vehicles, vans, tractors and trucks.

### **Ideal for onsite interventions**

✓ With its small size and 15kg weight, it is easily transportable on site and without effort.

√ 1.80 m of cables for optimal user comfort.

# For safe use

- ✓ Protection against polarities inversion thanks to an audible warning device and an indicator light.
- equipped with a fuse to protect vehicles against overvoltage, short circuits and avoid sparks when connecting the clamps
- ✓ Equipped with a 300 A fuse protecting the system by case of misuse.

# **Complete unsupervised charging**

✓ Thanks to its integrated automatic charger (6 A - curve 7-step intelligent charging), the Gyspack PRO 900 recharges 100% from the mains, unattended, even when permanently connected.

✓ Visualization of the state of charge thanks to three LEDs.

# **Memory backup function**

✓ 1 cigarette lighter socket for holding or saving vehicle memories (15 A fuse) when changing batteries.

## A protected cover

✓ The GYSPACK PRO 900 is equipped with corner pads. They protect the cover from impacts when working in demanding environments (on site or in the workshop).



#### **Intelligent charging curve: 7 steps**

After each

use



100-240

- 100% automatic charging
- Extends the life and performance of the internal battery

12 V	START			TEST TO	CHARGEUR PROTE		ECTION	POWER OUT			1.		
	<b>I</b> 1V/C	Crancking CC	Peak Battery		CHARGE 100-240 V	off F	<b>(</b> ) =	MEMORY			cm	kg	
12 V HAWKER 30 Ah	830A	1700 A	3100 A	•	6 A	•	•	12 V DC	15 A	2x1,80 m ø 35 mm²	31 x 32 x 16,5	15	