

The PROMAX 5-9/9-13 G TRUE COLOR is a compact and lightweight protection, ideal against light radiation, incandescent projections and welding or grinding sparks. Fully automatic, the mask switches from clear to tinted state in a fraction of a second as soon as it is primed. Comes with a headband, it frees the welder's hands and offers all the necessary comfort for welding work.

CARACTERISTICS

- Clear shade 4 with variable 5-9/9-13 settings
- Protection UV/ IR protection DIN 15
- Exterior settings : shades or grinding (Grind)
- Fast reaction speed 0.08 ms.
- Interior settings : sensitivity, delay.
- TRUE COLOR Technology



Classic LCD screen




LCD True color Technology




Delivered with headband Multift+

TECHNICAL

Protection UV/IR	DIN 15
Classification	1/1/1/2
Clear shade	3
Dark shade	5 > 9 - 9 > 13
Reaction speed	0,08 ms
Back to clear speed	0,10 > 0,8 sec
Field of vision	100 x 49 mm
Power supply	solar
Weight	560 g
Settings	Sensibility, delay, shade, grinding
Light sensors	2
Applications	MMA 5 ▶ 400 / TIG 5 ▶ 300 / MIG-MAG 5 ▶ 400
Standards	CE / EN 175F / EN 166 / EN 379



Sensibility



Delay



Shade

Grinding

OPTIONS


Carry bag for helmet welding

043299




Antiperspirant - headband

043466
x2



Lenses



226x 106 (x5)	045781
103.6 x 54 (x5)	077621