

The PROMAX 5-9/9-13 G TRUE COLOR is a compact and lightweight protection, ideal against light radiation, incandescent projections and welding or grinding sparks. Fully automatic, the mask switches from clear to tinted state in a fraction of a second as soon as it is primed. Comes with a headband, it frees the welder's hands and offers all the necessary comfort for welding work.

## CARACTERISTICS

- Clear shade 4 with variable 5-9/9-13 settings
- Protection UV/ IR protection DIN 15
- Exterior settings : shades or grinding (Grind)
- Fast reaction speed 0.08 ms.
- Interior settings : sensitivity, delay.
- TRUE COLOR Technology



Classic LCD screen




LCD True color Technology




Delivered with headband Multifit+

## TECHNICAL DATA

|                     |                                             |
|---------------------|---------------------------------------------|
| Protection UV/IR    | DIN 15                                      |
| Classification      | 1/1/1/2                                     |
| Clear shade         | 3                                           |
| Dark shade          | 5 > 9 - 9 > 13                              |
| Reaction speed      | 0,08 ms                                     |
| Back to clear speed | 0,10 > 0,8 sec                              |
| Field of vision     | 100 x 49 mm                                 |
| Power supply        | solar                                       |
| Weight              | 560 g                                       |
| Settings            | Sensibility, delay, shade, grinding         |
| Light sensors       | 2                                           |
| Applications        | MMA 5 ▶ 400 / TIG 5 ▶ 300 / MIG-MAG 5 ▶ 400 |
| Standards           | CE / EN 175F / EN 166 / EN 379              |



Sensibility



Delay



Shade

Grinding

### OPTIONS


Carry bag for helmet welding

043299




Antiperspirant - headband

043466  
x2



### Lenses



|                                                                                     |               |                                                                                       |               |
|-------------------------------------------------------------------------------------|---------------|---------------------------------------------------------------------------------------|---------------|
|  |               |  |               |
| 226x 106 (x5)                                                                       | <b>045781</b> | 103.6 x 54 (x5)                                                                       | <b>077621</b> |