

The GYSFLASH 125.12 CNT FV is a high-powered charger: 120 A continuously at 25°C. It allows to keep a 12 V lead or lithium battery at a perfectly stabilized voltage during the diagnostic phases. It will deliver the best charging cycle recommended for the maintenance of the most advanced vehicles on the market. Its USB connectivity makes it 100% customizable.

4 OPERATING MODES

- **Charging** : for 12 V Lead or Lithium (LFP) batteries from 20 to 1500 Ah.
- **Diagnostics** : supports up to 120 A for 12 V batteries in vehicles in the diagnostic phase, in maintenance workshops.
- **Showroom** : provides continuous power when using the electrical accessories of a demonstration vehicle. It also manages the optimal charging of the battery.
- **Tester** : Allows you to check the battery voltage, evaluate the starting system (starter + battery) and the condition of the vehicle's alternator.

100% CONNECTED

- Add, delete or modify charging modes and profiles via USB.
- Import predefined configuration files adapted to the load trades.
- Retrieve the charging history and data on a USB stick and use them on a spreadsheet.
- Connect additional modules (printer, barcode reader, etc.) via its dedicated module socket (SMC: Smart Module Connector).

AUTOMATIC CHARGE

- Extends the life and performance of Lead (gel, AGM, liquid, calcium, etc.) and Lithium (LFP) batteries.
- Specific charging curve in **8 steps** (lead battery) or **9 steps** (lithium-iron phosphate battery) without supervision.
- Recovers deeply discharged batteries >2 V (*automatic SOS Recovery*).

TECHNOLOGIES & ADVANCED FUNCTIONS

- **FV Flexible Voltage**, the charger operates with a supply voltage between 85 and 265 V.
- **«Auto-Detect»** function automatically starts a charge when a battery is connected to the charger.
- **«Auto-Restart»** function in the event of a power failure with memory of the settings.
- **Control and calibration of cables**
- **Locking**, avoids the risk of improper handling, ideal for garages and exhibition halls.
- Up to **12 charging profiles** available, including the Easy profile for simplified charging suitable for all lead batteries.

ULTRA-SECURE

- **Protection of the vehicle's on-board electronics**: protection against short circuits, polarity reversal and overcharging. Spark prevention system.
- **Replaceable fuse** which protects against misuse.
- **Temperature sensor** to prevent internal electronics overheating.

ERGONOMIC

- **Durable case** with shock and vibration absorbing pads.
- **IP40** enclosure, protected against the intrusion of objects larger than 1 mm.
- **Low height** (13 cm) for the loader to pass under a vehicle.



SMC USB




Supplied with cables (5 m - 25 mm²)



Intuitive interface available in 22 languages



ACCESSOIRES (optional)



Wall shelf
055513



Carry case
060432

compatible cables



Texas Cable > Pliers
028876 - 2.5 m - 25 mm²
027886 - 5 m - 25 mm²



Texas Cable > REMA
025714 - 5 m - 25 mm²



Texas Cable > Pliers
025721 - 5 m - 25 mm²



Texas Cable > NATO
025707 - 5 m - 25 mm²

50 / 60 Hz		V	I max	25°C @100%	40°C @100%	Charge	START MINI	IP	V L	mm ²	SHOWROOM CONNECT	kg	cm	L x W x H cm / kg
220 > 240 V	2000 W	2,5 m	12 V	230 V : 120 A	230 V : 120 A	230 V : 116 A	1 V	40	5 m	25	ø M6	6,3	33,4 x 13 x 28	41 x 39 x 22,5 / 10,8
100 > 127 V	1500 W			110 V : 100 A	110 V : 100 A	110 V : 77 A								