

The air-cooled 250A MIG/MAG welding torch is the perfect answer to the needs of welders carrying out a wide range of work on aluminium, guaranteeing consistent, foolproof welding. The non-slip coating and ball-and-socket joint on the handle make it exceptionally comfortable to work with.

Threaded nozzle for a firm hold and better heat dispersion.



Ergonomic handle for excellent grip.

Flexible cable with ball-and-socket joint to reduce wrist torsion.

HIGH PERFORMANCE

- Reliable, robust torch for perfect welding on all aluminium materials.
- Highly resistant to mechanical shocks and high temperatures.
- Smooth, jolt-free wire feed.
- Perfect compatibility with GYS equipment.
- Universal European connector (Euro).



Supplied in colour box
(380 x 310 x 75 mm)

FEATURES

Duty cycle	230 A at 60%*	
Cooling	air	
Compatible wire diameter	0.8-1.2 mm	
Original equipment	contact tube	Ø 1.0 mm - M6
	nozzle	Ø 15 mm
Applications	Thin sheet metal, light fabrication, locksmithing	
Cable	length	3 m
	section	25 mm ²






*In pulsed welding, the duty cycle is reduced by 35%.



MB 25

Optional consumables box
041233

CONSUMABLES (OPTIONS)

						
Inner sheath Ø 1.0/1.2 mm 3 m	Spring (x5)	Contact tube support (x5)	Contact tube (x10)			Nozzle (x3)
041585	042995	042919	Ø 0.8 mm 041059	Ø 1.0 mm 041066	Ø 1.2 mm 041073	041882