

The air-cooled TIG 17 welding torch is perfectly suited to the needs of welders carrying out a wide range of jobs, guaranteeing consistent, foolproof welding. The non-slip coating and ball-and-socket joint on the handle make it exceptionally comfortable to work with. Interchangeable buttons make it possible to adapt to all welders and turn the torch into a remote control for raising and lowering the welding current (Potentiometer / Up & Down).

## MODULAR DESIGN

The control modules can be changed at any time, in a matter of seconds, without the need for tools.



Single knob	Double knob	Knob + Potentiometer	Up & Down (2 buttons)	Up & Down (4 buttons)
084209	084216	084230	084223	089877



## HIGH PERFORMANCE








- Reliable, robust torch for perfect welding on all materials.
- Effective heat dissipation.
- Optional screen diffuser to ensure uniform gas distribution.
- Universal connector (Ø 35/50 mm Amphenol).

## FEATURES

Duty cycle	DC	140 A at 35 %
	AC	125 A at 35 %
Cooling	air	
Recommended electrode diameter	1.6 > 4.0 mm	
Original module	Single button	
Beam length	4 m	
Torch weight	1.8 kg	

## CONSUMABLES (options)

	
Cap (x1)	Vice grip (x3)
Short 044944	Ø 1.6 044982
Long 044951	Ø 2.0 044999
	Ø 2.4 045019
	Ø 3.2 045125
	Ø 4.0 047655

Standard			
			
Insulating ring (x1)	Collar support (x3)	Nozzle (x3)	
045040	Ø 1.6 044968	N4 Ø 6.5 038394	N10 Ø 16 045293
	Ø 2.0 044975	N5 Ø 8.0 045026	N12 Ø 19 045309
	Ø 2.4 044975	N6 Ø 9.5 038400	
	Ø 3.2 045118	N7 Ø 11 045033	
	Ø 4.0 047648	N8 Ø 12.5 045286	
Pro			
			
Insulating ring (x1)	Diffuser ring (x1)	Screen diffuser (x2)	Diffuser nozzle (x3)
045040	045095	Ø 1.6 045057	N5 Ø 8.0 045071
		Ø 2.0 045064	N7 Ø 11 045088
		Ø 2.4 045064	



Supplied in a coloured box (380 x 310 x 75 mm)



### TIG 17

Optional consumables box 044678