

The air-cooled TIG 26 welding torch is the perfect answer to the needs of welders working on a wide range of jobs, guaranteeing consistent, foolproof welding. The non-slip coating and ball-and-socket joint on the handle make it exceptionally comfortable to work with. Interchangeable buttons make it possible to adapt to all welders and turn the torch into a remote control for raising and lowering the welding current (Potentiometer / Up & Down).

MODULAR DESIGN

The control modules can be changed at any time, in a matter of seconds, without the need for tools.



Single knob	Double knob	Knob + Potentiometer	Up & Down (2 buttons)	Up & Down (4 buttons)
084209	084216	084230	084223	089877



HIGH PERFORMANCE








- Reliable, robust torch for perfect welding on all materials.
- Effective heat dissipation.
- Optional screen diffuser to ensure uniform gas distribution.
- Universal connector (Ø 35/50 mm Amphenol).

FEATURES

Duty cycle	DC	180 A at 35 %
	AC	150 A at 35 %
Cooling	air	
Recommended electrode diameter	1.6 > 4.0 mm	
Original module	Single button	
Beam length	4 m	
Torch weight	2.5 kg	

CONSUMABLES (options)

	
Cap (x1)	Vice grip (x3)
Short Long	Ø 1.6 Ø 2.0 Ø 2.4 Ø 3.2 Ø 4.0
044944 044951	044982 044999 045019 045125 047655

Standard			
			
Insulating ring (x1)	Collar support (x3)	Nozzle (x3)	
045040	Ø 1.6 044968 Ø 2.0 044975 Ø 2.4 044975 Ø 3.2 045118 Ø 4.0 047648	N4 Ø 6.5 038394 N5 Ø 8.0 045026 N6 Ø 9.5 038400 N7 Ø 11 045033 N8 Ø 12.5 045286	N10 Ø 16 045293 N12 Ø 19 045309
Pro			
			
Insulating ring (x1)	Diffuser ring (x1)	Screen diffuser (x2)	Diffuser nozzle (x3)
045040	045095	Ø 1.6 045057 Ø 2.0 045064 Ø 2.4 045064	N5 Ø 8.0 045071 N7 Ø 11 045088



Economical and durable thanks to its interchangeable knob

Ergonomic handle for excellent grip

Ball-and-socket cable to reduce wrist twisting



Supplied in a coloured box (380 x 310 x 75 mm)



TIG 26

Optional consumables box 044678