

The RC-HD4 is a multi-function wired remote control with digital display, for precise and instantaneous adjustment of the welding current. Lockable and easy to use, it is ideal for applications where you need to work away from the power source or in confined spaces.

### ADJUSTMENT AT YOUR FINGERTIPS

#### TIG mode:

- Welding intensity (0 to 100%).
- Gas purge: ideal for adjusting the gas flow on the pressure regulator.
- Trigger behaviour: 2T or 4T.
- UpSlope: duration of the current ramp up for arc ignition.
- DownSlope: duration of the current down slope to reduce the temperature of the weld pool.

#### MMA mode :

- Welding current (0 to 100%).
- HotStart: adjustable overcurrent to facilitate ignition.
- ArcForce: selective current increase for awkward welding situations.

### FEATURES

- Adjustable current thresholds (min and max).
- Screen brightness adjustable between 0 and 100%.
- Recall of up to 20 JOBS, stored on the power source, for recurring applications.
- Lock function to prevent accidental activation.
- Can be updated via the power source.

### ERGONOMIC

- Bright 1.54" colour LCD screen.
- Lightweight remote control (660 g) that's easy to manoeuvre, even when wearing gloves.
- Overhanging casing to minimise the risk of direct impacts on the screen.
- Screen protected by ultra-resistant anti-scratch film.
- Hole for attaching a safety strap.
- Magnetic spine for quick and easy attachment to metal surfaces.
- Extendable power cable up to 20 m for maximum flexibility.
- IP44-rated for use in humid or dusty environments.

### COMPATIBILITY





The RC-HD4 remote control is compatible exclusively with the GYS power sources which are equipped with a 7-pin digital Amphenol connector.

Find out about the compatible products by scanning this QR code or clicking on this [link](#).



#### Cable extension

2 m	079717
6 m	079724
10 m	079731

				<b>IP</b>
mm	kg	m	7 pins - Amphenol	IP 44
234 x 53 x 36	0.66	8 m		