

The air-cooled TIG 9 welding torch is perfectly suited to the needs of welders carrying out a wide range of jobs, guaranteeing consistent, foolproof welding. The non-slip coating and ball-and-socket joint on the handle make it exceptionally comfortable to work with. Interchangeable buttons make it possible to adapt to all welders and turn the torch into a remote control for raising and lowering the welding current (Potentiometer / Up & Down).

MODULAR DESIGN

The control modules can be changed at any time, in a matter of seconds, without the need for tools.



Single knob	Double knob	Knob + Potentiometer	Up & Down (2 buttons)	Up & Down (4 buttons)
084209	084216	084230	084223	089877

HIGH PERFORMANCE

- Lightweight, easy-to-handle torch.
- Ultra-compact head and accessories for easy welding in confined spaces.
- Optional mesh diffuser for uniform gas distribution.
- Universal connector (Ø 35/50 mm Amphenol).

FEATURES

Duty cycle	DC	110 A at 35 %
	AC	80 A at 60 %
Cooling	air	
Recommended electrode diameter	1.6 > 3.2 mm	
Original module	Single button	
Beam length	4 m	
Torch weight	1.9 kg	

CONSUMABLES (options)

Cap (x1)	Vice grip (x3)
Short 044814	Ø 1.6 044852
Long 044821	Ø 2.0 045132
	Ø 2.4 044869
	Ø 3.2 045255

Standard									
Insulating ring (x1)	Collar support (x3)	Nozzle (x3)							
044890	Ø 1.6 044838	N4 Ø 6.5	044876	N8 Ø 12.5	045170				
	Ø 2.0 045149	N5 Ø 8.0	038356	N10 Ø 16	038370				
	Ø 2.4 044845	N6 Ø 9.5	044883						
	Ø 3.2 045248	N7 Ø 11	038363						
Pro									
Insulating ring (x1)	Screen diffuser (x2)	Diffuser nozzle (x3)							
045095	Ø 1.6 044906	N4 Ø 6.5	044920						
	Ø 2.0 045156	N6 Ø 9.5	044937						
	Ø 2.4 044913	N7 Ø 11	045262						
	Ø 3.2 045279								

Economical and durable thanks to its interchangeable knob

Ergonomic handle for excellent grip

Ball-and-socket cable to reduce wrist twisting



Supplied in a coloured box (380 x 310 x 75 mm)



TIG 9

Optional consumables box 044654