

TIG 9 TORCH Pro

Ref. 084087 (4 m)

Ref. 084094 (8 m)



The air-cooled TIG 9 welding torch is ideal for welders working on a wide range of jobs, guaranteeing consistent, foolproof welding. The highly flexible harness ensures a comfortable grip and easy handling. Interchangeable buttons allow the torch to be adapted to all welders and transformed into a remote control for raising and lowering the welding current (Potentiometer / Up & Down).

MODULAR DESIGN

The control modules can be changed at any time, in a matter of seconds, without the need for tools.



Single button	Double button	Button + Potentiometer	Up & Down	Trigger
084247	084254	084278	084261	089266

HIGH PERFORMANCE

- Lightweight, easy-to-handle torch.
- Ultra-compact head and accessories for easy welding in confined spaces.
- Universal connector (Ø 35/50 mm Amphenol).

FEATURES

Duty cycle	DC	110 A at 35 %
	AC	80 A at 60 %
Cooling		air
Recommended electrode diameter		1.6 > 3.2 mm
Original module		Single button
Beam length		4 m or 8 m
Torch weight	4 m	1.9 kg
	8 m	3.4 kg

CONSUMABLES (options)

Cap (x1)	Vice grip (x3)
Short 044814	Ø 1.6 044852
Long 044821	Ø 2.0 045132
	Ø 2.4 044869
	Ø 3.2 045255

Standard					
Insulating ring (x1)	Collar support (x3)	Nozzle (x3)			
044890	Ø 1.6 044838	N4 Ø 6.5 044876	N8 Ø 12.5 045170		
	Ø 2.0 045149	N5 Ø 8.0 038356	N10 Ø 16 038370		
	Ø 2.4 044845	N6 Ø 9.5 044883			
	Ø 3.2 045248	N7 Ø 11 038363			
Pro					
Insulating ring (x1)	Screen diffuser (x2)	Diffuser nozzle (x3)			
045095	Ø 1.6 044906	N4 Ø 6.5 044920			
	Ø 2.0 045156	N6 Ø 9.5 044937			
	Ø 2.4 044913	N7 Ø 11 045262			
	Ø 3.2 045279				



Economical and durable thanks to its interchangeable knob

Ergonomically optimised handle for excellent grip

Ball-and-socket cable to reduce wrist twisting

Its protective leather sheath resists abrasion and ensures perfect glide over the forearm.

Cable resistant to daily twisting



Supplied in a coloured box (380 x 310 x 75 mm)

TIG 9

Optional consumables box 044654