BOOSTER
LITHIUM

12 V

NOMAD POWER PRO 701

Ref. 085855

INVEST IN THE FUTURE

NOMAD POWER 701 is a lithium-based power pack combining 3 functions:
- Booster pack for 12 V vehicles (car, SUV, light commercial vehicle, boat).
- Power bank for powering or charging all electronic devices.
- Emergency lamp.

LITHIUM BATTERY BOOSTER

The internal lithium battery has an exceptional power-to-size ratio (starting current: *700 A).*
It can start vehicles with discharged 12 V batteries (liquid, gel, AGM, stop-start) in just a few seconds (⚠ *cannot be used to start Lithium LiFePO4 vehicle batteries, as the voltages are not compatible*).

START	
12 V PETROL & DIESEL	5 › 140 Ah

SAFE STARTING

The intelligent starter cable protects both the battery and the electronic equipment in the vehicle:
- Anti-spark technology,
- Short-circuit protection,
- Anti polarity reversal technology.
- Excessive starting current protection,
- Thermal overload protection for the booster.

MOBILE ENERGY SOURCE

Its 4 Ah storage capacity offers convenience and reassurance for those who need to stay connected while on the move (phone, tablet, computer).

Equipped with:
- **2 USB ports 5 V - 2.1 A / 5/9/12 V - 2 A + 1 input/output USB Type C** *for recharging smartphones, tablets, GPS, etc.*
- **1 output port 15 V - 10 A**, *ideal for camping, to supply a 12 V electrical appliance (cooler, fan, etc.).*

EMERGENCY LIGHT

Single-LED lamp with 3 lighting modes: normal, strobe, SOS.

POCKET SIZE

Lightweight (820g) and compact, it fits neatly into the glove compartment or boot of your car, or into a travel bag.

Charging LED

Supplied with accessories:

Jump lead smart

Charging cable USB type C

Optional charger unit

087101 15 W USB charger

087354 15 W USB charger

STARTING						EQUIPMENT		INPUT / OUTPUT			POWER BANK	LED	DIMENSIONS	
Lithium			I			SMART CABLE	CABLES	INPUT	OUTPUT					
Capacity per cell	Type	Full charge	1 V/C	0 V/C	Peak Battery		USB-C			15 V Jack DC			cm	kg
4 Ah 59.2 Wh	$LiCoO_2$	3 h	700 A	1100 A	1250 A	✓	✓	USB-C 5 V - 3 A	3 — USB 3.0 QC: 5V-2.4A / 9V-2A / 12V-1.5 A; USB-A : 5V - 2.1A; SB-C: 5V - 3A	10 A	✓	3 modes: Light SOS Strobe	22.8 x 10 x 3.8	0.620

CE

MADE in China

www.gys.fr