

The air-cooled TIG 17 welding torch is ideal for welders working on a wide range of jobs, guaranteeing consistent, foolproof welding. The highly flexible harness ensures a comfortable grip and easy handling. Interchangeable buttons allow the torch to be adapted to all welders and transformed into a remote control for raising and lowering the welding current (Potentiometer / Up & Down).

MODULAR DESIGN

The control modules can be changed at any time, in a matter of seconds, without the need for tools.



Economical and durable thanks to its interchangeable knob

Ergonomically optimised handle for excellent grip

Ball-and-socket cable to reduce wrist twisting

Its protective leather sheath resists abrasion and ensures perfect glide over the forearm.

EURO connector

HIGH PERFORMANCE

- Lightweight, easy-to-handle torch.
- Optional sieve diffuser to ensure even gas distribution.

FEATURES

Duty cycle	DC	140 A at 35 %
	AC	125 A at 35 %
Cooling	air	
Recommended electrode diameter	1.6 > 4.0 mm	
Original module	Single button	
Beam length	4 m	
Torch weight	2 kg	





Supplied in a coloured box (380 x 310 x 75 mm)










TIG 17

Optional consumables box 044678

CONSUMABLES (options)

	
Cap (x1)	Vice grip (x3)
Short 044944	Ø 1.6 044982
Long 044951	Ø 2.0 044999
	Ø 2.4 045019
	Ø 3.2 045125
	Ø 4.0 047655

Standard					
					
Insulating ring (x1)	Collar support (x3)		Nozzle (x3)		
045040	Ø 1.6 044968	N4 Ø 6.5 038394	N10 Ø 16 045293		
	Ø 2.0 044975	N5 Ø 8.0 045026	N12 Ø 19 045309		
	Ø 2.4 044975	N6 Ø 9.5 038400			
	Ø 3.2 045118	N7 Ø 11 045033			
	Ø 4.0 047648	N8 Ø 12.5 045286			
Pro					
					
Insulating ring (x1)	Diffuser ring (x1)	Screen diffuser (x2)		Diffuser nozzle (x3)	
045040	045095	Ø 1.6 045057	N5 Ø 8.0 045071		
		Ø 2.0 045064	N7 Ø 11 045088		
		Ø 2.4 045064			